

Other models in this range:
MAR 56 - MAR 106 - MAR 126
MAR 206 - MAR 306
Split versions:
MAR 78 - MAR 128 - MAR 208
MAR 308

Scale Ice Maker Units up to 570 Kg



ABS Ice Chute Covermar: sold separately.



Gear box protection (hall effect)



Easy to remove water sump



Pulleys & belt system allows to modify ice thickness



Features

- Modular scale ice machine, production up to 570 Kg in 24h (@ 1 mm. ice thickness)
- Scale ice machine, in "compact system" version; built-in unit
- Storage bin not supplied, to be purchased separately
- AISI304 Stainless steel evaporator and ice scraper blade
- Redesigned evaporator compartment end-walls
- Foodgrade ABS plastic water sump tray, easy remove for cleaning and sanitising
- Electromechanical control panel
- Electrical protections, rotation speed & reverse phase controls
- Low- water sensor protection
- Hermetic compressor
- Choice of air or water cooled condenser
- Drive motor / gear reducer with V-Belt drive
- Storage bin thermostatic ice level sensor
- Stainless steel panels in scotch-brite finish, with rounded corners, easy to remove for maintenance


Accessories & Optional Features (to be specified upon order):

- Ice spout cover (COVERMARS0000)
- Ice chute extension 90cm (KICMAREXT0001)
- Double ice chute 65cm (KICMARDOUBL02)
- Infrared ice sensor (replaces the thermostatic ice level control) ICE SENSOR0003
- UV lamp water sanitising system for bacterial control (KITUVLAMPMARO)
- ON/OFF manual switch, with daily timer (KITTIMER0001)
- ON/OFF manual switch, with weekly programmable timer (KITTIMERSET01)

MAR 76 Technologies



	 24h THICK ICE	 THIN ICE	 NOMINAL ONLY	 [WxDxH mm] 906x813x1125 [WxDxH inches] 35 11/16 x 32 x 44 5/8	
	 2 mm [kg] [lbs]	 1 mm [kg] [lbs]	 0.5 mm [kg] [lbs]	 [v/Hz/ph] 400/50/3N R 404 A	
MAR 76 AS	510 1124	570 1257	740 1631		
MAR 76 WS	510 1124	570 1257	740 1631		



This product qualifies for the following listings:



2 Years Warranty

Subject to certain limitations and exclusions



Humidity 2%

Ice scales are the coldest form of ice. Formed at -6° to -12°Celsius, they are very dry, containing less than 2% residual water. Scales look like fragments of glass, have an irregular shape and a thickness that can be adjusted at 1 or 2 mm.


Certified ISO 9001:2000

www.scotsman-ice.it
www.scotsman-ice.com
www.scotsman-ice-on-tablet.com

Models and specifications are subject to change without notice.

Other models in this range:
MAR 56 - MAR 106 - MAR 126
MAR 206 - MAR 306
Split versions:
MAR 78 - MAR 128 - MAR 208
MAR 308

Scale Ice Maker Units up to 570 Kg



MAR 76 AIR COOLED

°C \ °F	50° 10°	60° 15°	70° 21°	90° 32°	
10°	510	500	485	460	kg
50°	1124	1102	1069	1014	lbs
21°	460	450	440	415	kg
70°	1014	992	970	915	lbs
32°	420	405	395	370	kg
90°	926	893	871	816	lbs
38°	390	375	365	340	kg
100	860	827	805	750	lbs



WITH THICK ICE SETTINGS

MAR 76 WATER COOLED

°C \ °F	50° 10°	60° 15°	70° 21°	90° 32°	
10°	510	500	485	460	kg
50°	1124	1102	1069	1014	lbs



WITH THICK ICE SETTINGS



Minimum

10°C (50°F)



Maximum

40°C (104°F)

5°C (41°F)



35°C (95°F)

-10%



+10%

1 BAR
14 psi



5 BAR
70 psi

	Standard TE (T cond.+54,5°C - T evap.-23,3°C)	[W]	[Btu/h]	[Ø mm²] [AWG]	[W]	FUSE	[kWh] - 100 Kg	[l/h]	[gal/h]	[kg] [lbs]	[kg] [lbs]
MAR 76 AS		2250	7670	5x1,5 AWG15	2500	16 A	15,2	16,5	3,3	187 412	204 449
MAR 76 WS		2250	7670	5x1,5 AWG15	2500	16 A	12,4	330	87,2	184 405	201 442